



**Tilling plus planting or seeding in one pass!**

# VARIX F





Self-cleaning top cover on springs



VariX 4500F foldable



Hydraulic cleaning kit (optional)

## VARIX F front cultivator

With a rotor diameter of Ø 660 mm, the VariX F creates enough loose soil for seedbed preparation. This loose soil largely determines the volume and height of the ridge. The ridge hillers are dismountable, meaning the VariX F can also be used for flat full-field seedbed tillage.

The VariX F is equipped as standard with 108 widia 30RC hooks mounted in random order. These distribute soil evenly across the entire working width and prevents jacking.

This cultivator comes with a top cover mounted on springs to prevent soil loading inside. Cylinders can also be fitted to clean the interior during operation. There are two benefits with this option - reduced power demand and less hook wear. As standard, the VariX F is equipped with a 1000 rpm gearbox, which can transmit up to 220 hp.

Optional extras:

- 280 hp gearbox rotor speeds 387 / 447 rpm
- Levelling beam
- V-shaped crumbler roll
- Hydraulic cleaning kit



Pin-hole adjustment crumbler roll



Pressure adjustment

## Dimensions and weights

Type	 min.			 rpm 12/16 (2.43)	 rpm 13/15 (2.43)	 rpm 12/20 (1.94)	 rpm 12/16 (1.94)	 rpm 13/15 (1.94)	 kg
VARIX 3000F	110hp/81kW	3050	4x75cm/4x30"	309	357	-	387	447	1360
VARIX 3600F	125hp/92kW	3650	4x90cm/4x36"	309	357	-	387	447	1600
VARIX 4500F	180hp/133kW	4550	6x75cm/6x30"	-	-	309	387	447	2500

Illustrations, dimensions and weights may be altered without prior notice.